



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar
Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2
Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	48,5	
3,00 mm	h 7	31,8	
4,00 mm	h 7	80,5	(100,0)
5,00 mm	h 7	85,9	(100,0)
6,00 mm	h 8	478,5	(300,0)
8,00 mm	h 8	1,6	(300,0)
10,00 mm	h 8	164,0	(900,2)
12,00 mm	h 8	472,4	
14,00 mm	h 8	308,4	
15,00 mm	h 8	12,3	(300,0)
16,00 mm	h 9	53,6	(500,0)
18,00 mm	h 9	662,3	
20,00 mm	h 9	449,5	(250,0)
22,00 mm	h 9	453,5	(300,0)
25,00 mm	h 9	672,8	(3000,0)
30,00 mm	h 9	1569,1	(500,0)
35,00 mm	h 9	314,1	(700,0)
40,00 mm	-0/+0.100	1076,4	(1200,0)
45,00 mm	-0/+0.100	122,7	(400,0)
50,00mm	-0/+0.100	960,4	(200,0)
55,00 mm	-0/+0.100	1818,4	
60,00 mm	-0/+0.120	1849,8	
65,00 mm	-0/+0.120	473,6	
70,00 mm	-0/+0.140	81,2	(400,0)
80,00 mm	-0/+0.140	590,5	
90,00 mm	-0/+0.200	35,8	(360,0)
100,00 mm	-0/+0.500	317,4	(106,0)
110,00 mm	-0/+0.500	245,5	
120,00 mm	-0/+0.500	74,7	(200,0)
130,00 mm	-0/+0.500	3,6	(720,0)
140,00 mm	-0/+0.500	41,4	(1040,0)
150,00 mm	-0/+0.500	35,0	(480,0)
160,00 mm	-0/+0.500	127,8	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
170,00 mm	-0/+0.500	429,2	
180,00 mm	-0/+0.500	231,0	
190,00 mm	-0/+0.500	107,3	(260,0)
200,00 mm	-0/+0.500	212,6	
225,00 mm	-0/+0.500	327,8	
250,00 mm	-0/+0.500	263,2	
280,00 mm	-0/+0.500	191,0	(278,0)
305,00 mm	-0/+0.500	332,8	
305,00 mm	-0/+0.500	0,0	(310,0)
350,00 mm	-0/+0.500	54,6	(350,0)

Titanium Grade 4 Round bar

Spec: ASTM B348 / ASME SB348 / ISO5832-2 / ASTM F67

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
100,00 mm	-0/+0.500	328,0	
130,00 mm	-0/+0.500	236,8	

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	42,3	
3,00 mm	h 7	128,1	
4,00 mm	h 7	1,4	(600,0)
5,00 mm	h 7	1,1	(700,0)
6,00 mm	h 8	513,9	(800,0)
8,00 mm	h 8	16,4	(400,0)
10,00 mm	h 8	51,8	(800,0)
12,00 mm	h 8	168,5	(700,0)
14,00 mm	h 8	29,2	(300,0)
15,00 mm	h 8	91,1	(300,0)
16,00 mm	h 9	390,1	(300,0)
18,00 mm	h 9	355,0	(200,0)
20,00 mm	h 9	281,2	(1100,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
22,00 mm	h 9	209,6	
25,00 mm	h 9	1155,0	(600,0)
25,00 mm	h 9	132,2	(300,0)
30,00 mm	h 9	103,7	
35,00 mm	h 9	310,2	(800,0)
36,00 mm	h 9	67,5	(400,0)
40,00 mm	-0/+0.100	673,6	(2500,0)
40,00 mm	-0/+0.100	673,3	(2500,0)
45,00 mm	-0/+0.100	502,0	(200,0)
50,00 mm	-0/+0.100	1367,9	(150,0)
55,00 mm	-0/+0.100	284,1	
60,00 mm	-0/+0.120	216,2	(600,0)
65,00 mm	-0/+0.120	35,8	(300,0)
70,00 mm	-0/+0.140	452,8	
75,00 mm	-0/+0.140	375,1	(300,0)
80,00 mm	-0/+0.140	539,4	
90,00 mm	-0/+0.200	421,3	
100,00 mm	-0/+0.500	1198,6	
110,00 mm	-0/+0.500	72,2	(400,0)
120,00 mm	-0/+0.500	485,7	
130,00 mm	-0/+0.500	640,9	(500,0)
140,00 mm	-0/+0.500	92,7	(420,0)
150,00 mm	-0/+0.500	290,1	
160,00 mm	-0/+0.500	119,3	(270,0)
170,00 mm	-0/+0.500	499,8	
180,00 mm	-0/+0.500	411,1	
190,00 mm	-0/+0.500	195,6	
200,00 mm	-0/+0.500	231,6	
225,00 mm	-0/+0.500	11,0	
230,00 mm	-0/+0.500	331,0	
250,00 mm	-0/+0.500	195,6	
280,00 mm	-0/+0.500	66,2	(140,0)
305,00 mm	-0/+0.500	208,8	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
350,00 mm	-0/+0.500	255,2	

Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASME SB 265 Gr1 edition 2015 DIN 17860 / NACE

MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Condition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
0,6 x 1000 x 2500	831,0	
0,8x 1000 x 2500	1136,6	
1,0 x 1250 x 3000	2237,4	(1000,0)
1,5 x 1250 x 3000	926,7	(500,0)
2,0 x 1250 x 3000	198,6	
2,0 x 1250 x 3000	1800,9	
2,5 x 1250 x 3000	212,6	
3,0 x 1250 x 3000	866,3	
4,0 x 1000 x 2000	106,8	(800,0)
5,0 x 1000 x 2000	234,5	(200,0)
6,0 x 1000 x 2000	0,0	(250,0)

Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017

PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
1,0x1000x2000	190,6	(300,0)
1,0x1000x2000	8,2	
1,5x1000x2000	586,0	
2,0x1000x2000	895,8	(1000,0)
3,0x1000x2000	558,4	(1000,0)
4,0x1000x2000	0,0	(944,0)
5,0x1000x2000	378,1	
5,0x1000x2000	0,0	(500,0)

Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
-----------	----------	----------



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 sheets
Spec: ASTM B265/ASME SB265
Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
1 x 1000 x 2000	141,1	
1 x 1000 x 2000	105,9	(100,0)
2 x 1000 x 2000	125,0	(200,0)
3 x 1000 x 2000	80,0	(400,0)
3 x 1250 x 2500	41,6	
4 x 1000 x 2000	0,0	(200,0)
5 x 1000 x 2000	91,6	(150,0)

Titanium Grade 2 Profiles
Spec: ASTM B265
Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
9,5 x 9,5	106,0	
12,7 x 12,7	127,8	
19,05 x 19,05	136,2	
25,4 x 6,35	151,0	
25,4 x 12,7	312,2	
25,4 x 25,4	218,2	

Titanium Grade 2 Welding wire
AWS A5.16 ERTi-2

Dimension	QTY (kg)	Incoming
1,2 mm	15,0	
1,2 mm	10,0	
2,0 mm	10,0	(30,0)
2,4 mm	5,0	(30,0)
3,2 mm	15,0	(20,0)

Titanium Grade 5 Welding wire
AWS A5.16 ERTi-5

Dimension	QTY (kg)	Incoming
1,6 mm	10,0	
2,4 mm	10,0	